

Test Report No: 7191219009-EEC19/01
dated 10 September, 2019

Note: This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.



PSB Singapore

**Add value.
Inspire trust.**

Applicant : BENITHEM SDN BHD
PTD 10710, JALAN KG AIR PUTIH, JALAN SAWAH,
81500 PEKAN NANAS, JOHOR,
MALAYSIA
ATTN: TAN CHIN TECK

Date Received : 05/08/2019

Test Period : 05/08/2019 - 10/09/2019

Sample Description : OFFICE CHAIR

Model Style : FEIN

Country Of Origin : MALAYSIA

Classification : TYPE I (WHEN TILT MECHANISM IS UNLOCKED)
: TYPE III (WHEN TILT MECHANISM IS LOCKED)

Manufacturer : BENITHEM SDN BHD



Laboratory:
TÜV SÜD PSB Pte. Ltd.
No.1 Science Park Drive
Singapore 118221

Phone : +65-6885 1333
Fax : +65-6776 8670
E-mail: enquiries@tuv-sud-psb.sg
www.tuv-sud-psb.sg
Co. Reg : 199002667R

Regional Head Office:
TÜV SÜD Asia Pacific Pte. Ltd.
1 Science Park Drive, #02-01
Singapore 118221
TÜV®

SAMPLE PHOTO



EXECUTIVE SUMMARY:


The sample(s) **MEETS** the following requirement(s):

- The requirement of ANSI/BIFMA X5.1-2017 General-Purpose Office Chairs - Tests

For any concern or technical Inquiries, please contact

KOO CHIEH VOON
HARDLINE PRODUCT MANAGER
Tel: +65 6885 1554
Email: Chieh-Voon.KOO@tuv-sud-psb.sg

PERFORMED BY:



WONG KOK LEONG
TEAM LEADER

APPROVED BY:



KOO CHIEH VOON
HARDLINE PRODUCT MANAGER

Test Report No: 7191219009-EEC19/01
dated 10 September, 2019



TEST RESULT(S):

Clause	Test	Parameters	Results	Requirement
5	Back Strength Test – Static – Type I	Functional load = 667 N Proof load = 1,001 N Duration = 1 min	Pass	Functional load: No loss of serviceability Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable
6	Back Strength Test – Static – Type II & III	Functional load = 667 N Proof load = 1,001 N Duration = 1 min	Pass	
7	Drop Test – Dynamic	Highest seat position: Functional load = 102 kg Proof load = 136 kg Drop ht = 152 mm Lowest seat position: Functional load = 102 kg Proof load = 136 kg Drop ht = 152 mm	Pass	Functional load: No loss of serviceability Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable
8	Swivel Test – Cyclic	Seat load = 122 kg Total cycles = 120,000 • 60,000 highest position • 60,000 lowest position Rate = 5 - 15 cycles/min	Pass	No loss of serviceability
9	Tilt Mechanism Test – Cyclic	Chair height: Mid-point Seat load = 109 kg Cycles = 300,000 Rate = 10 - 30 cycles/min	Pass	No loss of serviceability to the tilt mechanism
10	Seating Durability Tests – Cyclic a) Impact Test	Chair height: Mid-point Unlocked Seat load = 57 kg Drop ht = 36 mm Cycles = 100,000 Rate = 10 - 30 cycles/min	Pass	No loss of serviceability. If applicable, the chair base (center structure) shall not touch the test platform as a result of the impact loads.
	b) Front Corner Load-Ease Test – Cyclic – Off Center	Chair height: Mid-point Seat load = 890 N Cycle = 40,000 Rate = 10 - 30 cycles/min	Pass	

TEST RESULT(S): continued

Clause	Test	Parameters	Results	Requirement
11	Stability Tests:	i) Type I & II Loading = 13 disks	Pass	Chair shall not tip over.
	a) Rear Stability	ii) Type III Loading = 6 disks Seat height ≤ 710 mm, Force = 0.1964(1195 - <u>518</u>) = <u>133</u> N	Pass	
	b) Front Stability	Vertical Load = 61kg Horizontal force = 20 N	Pass	
12	Arm Strength Test – Vertical – Static	Functional load = 750 N Duration = 1 min Proof load = 1,125 N Duration = 15 sec	Pass	Functional load: No loss of serviceability. For a height adjustable arm, it must hold the position within 6mm. Proof Load: No sudden & major change in structural integrity. For a height adjustable arm, it must not has a sudden drop in height of greater than 25mm. Loss of serviceability is acceptable
13	Arm Strength Test – Horizontal – Static	Functional load = 445 N Duration = 1 min Proof load = 667 N Duration = 15 sec	Pass	Functional load: No loss of serviceability. Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable
14	Back Durability Test – Cyclic – Type I	Seat weight = 109 kg Loading force = 445 N Cycles = 120,000 Rate = 10 - 30 cycles/min	Pass	No loss of serviceability
15	Back Durability Test – Cyclic – Type II & III	Seat weight = 109 kg Loading force = 334 N Cycles = 120,000 Rate = 10 - 30 cycles/min	Pass	
16	Caster / Chair Base Durability Test – Cyclic	Seat weight = 122 kg Cycles: 2,000 (Obstacles) 98,000 (No obstacles) Rate = 10 ± 2 cycles/min	Pass	
	- Pedestal Base Chairs		Not Applicable	
	- Non-pedestal chairs with casters			
	Caster Retention for each caster	Applied force = 22N	Pass	No part of caster shall separate from base

TEST RESULT(S): continued

Clause	Test	Parameters	Results	Requirement
17	Leg Strength Test – Front & Side Application - Front Load Test	Functional load = 334N Proof load = 503N Duration = 1 min (each front leg)	Pass	Functional load: No loss of serviceability Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable
	- Side Load Test	Functional load = 334N Proof load = 503N Duration = 1 min (front and rear leg)	Pass	
18	Footrest Static Load Test – Vertical	Functional Load, Force, F1 = Footrest adjustment, Force F1 = Force, F2 = Duration =	Not Applicable	Functional Load: No loss of serviceability or sudden loss of footrest height. Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable
		Proof Load, Force = Duration =	Not Applicable	
19	Footrest Durability Test – Vertical – Cyclic	Loading force = Cycles = Rate =	Not Applicable	No loss of serviceability. Adjustable footrest that move more than 25mm in the first 500 cycles shall be considered to have lost their serviceability.
20	Arm Durability Test – Cyclic	Applied force = 400 N Cycles = 60,000 Rate = 10 - 30 cycles/min	Pass	No loss of serviceability.
21	Out Stop Tests for Chairs with Manually Adjustable Seat Depth	Seat weight = 74 kg Loading weight = 25 kg Cycles = 25	Pass	
22	Tablet Arm Static Load Test	Applied load = Duration =	Not Applicable	No sudden and major change in the structural integrity of the chair. After test, tablet arm must allow egress from the unit; other losses of serviceability are acceptable
23	Tablet Arm Load Ease Test – Cyclic	Force = Cycles = Rate =	Not Applicable	No loss of serviceability

TEST RESULT(S): continued

Clause	Test	Parameters	Results	Requirement
24	Structural Durability Test – Cyclic	Seat weight = 109 kg Force = 334 N Cycles = 25,000 Rate = 10 - 30 cycles/min	Not Applicable	No loss of serviceability.
Appendix C	Base Test – Static	Loading force = 11.1 kN Duration = 1 min Cycles = 2	Pass	No sudden & major change in the structural integrity of the base.
Appendix H	Simultaneous Side Legs Strength Test	Force = 334 N Duration = 1 min (front and rear leg simultaneously)	Pass	No loss of serviceability.



Please note that this Report is issued under the following terms :

1. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
2. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
3. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
4. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
5. Unless otherwise stated, the tests were carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

July 2011

